

# Plain Plug Gauges (PPG)

HSN90173021



PPG used as Go NoGo gauge (Reversible Plug gauge & Taper Lock PPG).

We are manufacturing plug are highly polished-mirror Surface Finish.

Specifications:-

Material – En 31(SAE52100), OHNS, Tungsten Carbide.

Tolerance - On Dia. +/- 0.001 mm

PLUG GAUGES FROM THE RANGE 0.5MM TO 6MM WILL BE REVERSIBLE TYPE. PLUG GAUGES FROM 6.0MM TO 40.0MM WILL BE TAPER LOCK TYPE (DOUBLE ENDED). PLUG GAUGES FROM 40 MM TO 80.0MM WILL BE DISC TYPE (DOUBLE ENDED) .PLUG GAUGES FROM 80MM TO 100MM WILL BE DISC TYPE (SINGLE ENDED). PLUG GAUGES FROM 100MM AND ABOVE WILL BE PLATE TYPE (SINGLE ENDED) GO PLATE 16MM X 32MM, NOGO PLATE 20MM X 20MM

Calibration –

All Pins are Calibrated @ 20°C Under Standards Room Conditions Traceable To National . standard Of length.

Calibration Instrument -

Mitutoya ( made in Japan) Slip box . Range 1.0005 to 100.00 mm.& mahr (made in Germany) Dial gauge with Accuracy 0.001 mm and range ±50 microns.